

# Wheeled Rod Guide™ Couplings by Oilfield Improvements, Inc.

## PRICE LIST

Effective June 1, 2010

### Standard Model, with Power Tong Flats FOR NON-CORROSIVE ENVIRONMENT

Model No. and Applications(1)	Maximum Rod Load (2)	Dimensions			Weight	Unit Price
		A"	B"	C"		
2058P 2-3/8" Tubing 5/8" Rod	19,600	1.5	27	1.8	10 lbs.	\$164.00
2034P 2-3/8" Tubing 3/4" Rod	19,600	1.5	27	1.8	10 lbs.	\$164.00
2558P 2-7/8" Tubing 5/8" Rod	19,600	1.5	27	2.25	10 lbs. 2 oz.	\$171.00
2534P 2-7/8" Tubing 3/4" Rod	19,600	1.5	27	2.25	10 lbs.	\$171.00
2578P 2-7/8" Tubing 7/8" Rod	22,400	1.625	27	2.25	11 lbs. 5 oz.	\$182.00
2510P 2-7/8" Tubing 1" Rod	32,500	2	28.5	2.25	18 lbs. 2 oz.	\$210.00
3034P 3-1/2" Tubing 3/4" Rod	19,600	1.5	28.5	2.75	12 lbs 6 oz.	\$195.00
3078P 3-1/2" Tubing 7/8" Rod	22,400	1.75	28.5	2.75	15 lbs.	\$205.00
3010P 3-1/2" Tubing 1" Rod	32,500	2	28.5	2.75	19 lbs.	\$210.00
30112P 3-1/2" Tubing 1-1/8" Rod	49,000	2.25	28.5	2.75	22 lbs 2 oz.	\$245.00

### Stress Proof Model, with Power Tong Flats FOR USE WITH HIGH-STRESS RODS

Model No. and Applications(1)	Maximum Rod Load (2)	Dimensions			Weight	Unit Price
		A"	B"	C"		
1558SP 1-1/2" Tubing 5/8" Rod	19,600	1.25	22	1.625	5 lbs. 11 oz.	\$172.00
2034SP 2-3/8" Tubing 3/4" Rod	26,000	1.5	27	2.25	10 lbs. 2 oz.	\$204.00
2078SP 2-3/8" Tubing 7/8" Rod	25,500	1.625	27	1.8	10 lbs.	\$221.00
2534SP 2-7/8" Tubing 3/4" Rod	26,000	1.5	27	2.25	10 lbs.	\$204.00
2578SP 2-7/8" Tubing 7/8" Rod	31,000	1.625	27	2.25	11 lbs. 5 oz.	\$214.00
2510SP 2-7/8" Tubing 1" Rod	42,000	2	28.5	2.25	18 lbs. 2 oz.	\$334.00
3034SP 3-1/2" Tubing 3/4" Rod	26,000	1.5	28.5	2.75	12 lbs. 6 oz.	\$233.00
3078SP 3-1/2" Tubing 7/8" Rod	31,000	1.75	28.5	2.75	15 lbs.	\$247.00
3010SP 3-1/2" Tubing 1" Rod	42,000	2	28.5	2.75	19 lbs.	\$334.00
4010SP 4-1/2" Tubing 1" Rod	42,000	2.1875	33.5	3.75	25 lbs. 7 oz.	Call

(1) Temperatures Caution  
Standard models are for applications in well bore  
Temperatures up to 175° F. (fitted with ultra high  
molecular weight polyethylene wheels). For service  
in higher temperatures, see special wheels listed  
on reverse side and consult  
Oilfield Improvements, Inc.

(2) Rod Load Caution  
Standard models are designed for application  
within these listed Rod Load Limits. For  
applications exceeding these limits, consult Oilfield  
Improvements, Inc. Oilfield Improvements, Inc.  
does not express or imply any warranties of its  
Wheeled Rod Guide™ Couplings, either with regard  
to Rod Load Limits or in any other manner.



™

## Oilfield Improvements, Inc.

1902 N. Yellowwood Ave. • Broken Arrow, OK 74012

(918) 250-5584 • 800-537-9327 • FAX (918) 250-4666

[info@rodguides.com](mailto:info@rodguides.com) [www.rodguides.com](http://www.rodguides.com)

Copyright © 2010 Oilfield Improvements, Inc.